RECEIVED
CENTRAL FAX CENTER
MAY 0 8 2008

Amendments to the Claims:

There are no amendments to the claims.

Status of Claims:

Claims 1-39 are pending for examination.

Claims 1, 33, 37 & 38 are in independent form.

1. (Original) A system, comprising:
   an information receiving logic configured to receive an information signal;
   a driven element configured to transmit an outbound information signal at a predetermined power and a predetermined frequency that create a transmission zone that is less than forty eight inches in a plane; and
   a transmission line configured to facilitate transferring a first intermediate signal, from which the outbound information signal is derived, from the information receiving logic to the driven element;
   where at least one of the information receiving logic, the driven element, and the transmission line are integrated into a PVLAN-space element.

2. (Original) The system of claim 1, including a shield configured to mold the transmission zone, where the shield is integrated into a PVLAN-space element.

3. (Original) The system of claim 1, including a shield configured to at least partially block electromagnetic radiation from entering the transmission zone, where the shield is integrated into a PVLAN-space element.

4. (Original) The system of claim 1, including a shield configured to at least partially block the outbound signal from leaving the transmission zone, where the shield is integrated into a PVLAN-space element.

5. (Original) The system of claim 1, the information signal comprising one or more of, a telephone signal, a television signal, a computer signal, a data signal, a facsimile signal, a DSL signal, a broadcast signal, a GPS signal, and a radio signal.

6. (Original) The system of claim 5, the telephone signal comprising one or more of, an analog telephone signal, a digital telephone signal, an analog cellular telephone signal, and a digital cellular telephone signal.

7. (Original) The system of claim 5, the television signal comprising one or more of, an over the air television signal, a cable television signal, a digital television signal, and a satellite television signal.

8. (Original) The system of claim 5, the computer signal comprising one or more of, an IEEE 802.3 signal, an IEEE 802.5 signal, an IEEE 802.11 signal, and an IEEE 802.15.1 signal.

9. (Original) The system of claim 5, the radio signal comprising one or more of, an AM signal, an FM signal, an XM signal, and a shortwave signal.

10. (Original) The system of claim 1, the PVLAN-space element comprising one or more of, a desktop, a tabletop, a desk, a table, a cubicle wall, a cubicle, an office wall, an office, a wall, and a cabinet.

11. (Original) The system of claim 1, the driven element comprising one or more of, an omni directional antenna, a yagi antenna, a horn antenna, a spiral antenna, a helical antenna, a loop antenna, a blade antenna, a flat panel antenna, and a sector antenna.

12. (Original) The system of claim 1, the driven element being configured to transmit the outbound information signal in a power range from about 0.01 mW to about 0.1 W.

13. (Original) The system of claim 1, the driven element being configured to transmit the outbound information signal in a frequency range from about 500 MHz to about 1.5 GHz.

14. (Original) The system of claim 1, where the outbound signal is intended for an electronic device comprising one or more of, a computer, a telephone, a facsimile machine, a monitor, a PDA, a keyboard, a radio, and a GPS.

15. (Original) The system of claim 1, comprising a receiver configured to receive an inbound information signal from an electronic device.

16. (Original) The system of claim 15, the transmission line being further configured to facilitate transferring a second intermediate signal derived from the inbound information signal from the receiver to the information receiving logic.

17. (Original) The system of claim 15, the receiver comprising one or more of, a super heterodyne receiver and a co-axial receiver.

18. (Original) The system of claim 1, the transmission line comprising one or more of, a coaxial cable, a low loss cable, a fiber optic cable, a SCSI cable, a LAN cable, an elliptical waveguide cable, a rectangular waveguide cable, a ribbon cable, a CAT 5e cable, a CAT 6 cable, a shielded twisted pair cable, and an unshielded twisted pair cable.

19. (Original) The system of claim 2, the shield comprising one or more of, a faraday cage, a copper mesh screen, a welded sheet aluminum plate, a metal textile shield, a plastic film, a wire mesh, a brass plate, a tin plated steel plate, a nickel silver plate, a conductive fabric, and a conductive paint.

20. (Original) The system of claim 3, the shield comprising one or more of, a faraday cage, a copper mesh screen, a welded sheet aluminum plate, a metal textile shield, a plastic film, a wire mesh, a brass plate, a tin plated steel plate, a nickel silver plate, a conductive fabric, and a conductive paint.

21. (Original) The system of claim 4, the shield comprising one or more of, a faraday cage, a copper mesh screen, a welded sheet aluminum plate, a metal textile shield, a plastic film, a wire mesh, a brass plate, a tin plated steel plate, a nickel silver plate, a conductive fabric, and a conductive paint.

22. (Original) The system of claim 2, where the shield is grounded.

23. (Original) The system of claim 2, where the shield is bonded to a 0.01 ohm to digital ground connection.

24. (Original) The system of claim 3, where the shield is grounded.

25. (Original) The system of claim 3, where the shield is bonded to a 0.01 ohm to digital ground connection.

26. (Original) The system of claim 4, where the shield is grounded.

27. (Original) The system of claim 4, where the shield is bonded to a 0.01 ohm to digital ground connection.

28. (Original) The system of claim 1, comprising:

an override panel configured to provide access to one or more wired connections by which the information signal can be received.

29. (Original) The system of claim 28 where the override panel includes one or more of, a video port, an RS232 port, an RS 422 port, an RJ45 port, an RJ11 port, an XLR connector, a LAN connector, and a BNC connector.

30. (Original) The system of claim 1, where the information receiving logic, the driven element, and the transmission line are integrated into a single PVLAN-space element.

31. (Original) The system of claim 1, comprising:

an effective zone indicator configured to visually illustrate a boundary associated with the transmission zone.

32. (Original) The system of claim 31, where the effective zone indicator is located on a PVLAN-space element surface.

33. (Original) A method, comprising:

receiving an information signal;

selectively deriving an intermediate signal from the information signal;

selectively relaying the intermediate signal to a driven element;

transmitting an outbound information signal derived from the intermediate signal from the driven element at a designated power output and designated frequency, where the combination of designated power and designated frequency produce a limited zone of less than forty eight inches; and

positioning one or more shields to perform one or more of, molding the size of the limited zone, molding the shape of the limited zone, protecting the limited zone from RF interference, and limiting interference produced by transmitting the outbound information signal.

34. (Original) The method of claim 33, the information signal comprising one or more of, a telephone signal, a television signal, a computer signal, a facsimile signal, an internet signal, a DSL signal, a broadcast signal, a GPS signal, and a radio signal.

35. (Original) The method of claim 33, where the outbound information signal is transmitted with a power of about 0.01 mW to about 1 mW.

36. (Original) The method of claim 35, where the outbound information signal is transmitted with a frequency of about 500 MHz to about 1.5 GHz.

37. (Original) A piece of furniture, comprising:
an information receiving logic configured to receive an information signal;
a driven element configured to transmit an outbound information signal at a predetermined power and a predetermined frequency that create a transmission zone that is less than forty eight inches in a plane;
a transmission line configured to facilitate transferring a first intermediate signal, from which the outbound information signal is derived, from the information receiving logic to the driven element;
a shield configured to perform one or more of, molding the transmission zone, to at least partially block electromagnetic radiation from entering the transmission zone, and to at least partially block the outbound signal from leaving the transmission zone; and
an override panel configured to provide access to a wired connection by which the information signal can be received;
where the information receiving logic, the driven element, the transmission line, the override panel, and the shield are integrated into the piece of furniture.

38. (Original) A method of altering a piece of furniture, comprising:
providing a shielding material configured to affect the transmission of electromagnetic radiation; and
integrating the shielding material into the piece of furniture.

39. (Original) The method of claim 38, comprising:

providing a driven element configured to transmit a PVLAN signal by electromagnetic radiation; and

integrating the driven element into the piece of furniture.